



**PREMIUM PRODUCT**

# HKPARK LED

**Outdoor Product, High resolution LED High strength cabinet to be installed on the ground or on the roof/ Outdoor installation for banks , entrance to commercial stores, universities, temples, parking etc. / Includes 2 free height 1m legs (you can request a measure of your choice) / Useful life greater than 100,000 HS Can be manufactured in measures**

**ENTRY LEVEL:**

-  Low Consumption
-  Resistant Cabinet
-  Outdoor Installator
-  Spectacular Colors
-  Wide Viewing Angle
-  High Refresh Rate



## INDOOR MODELS

HK WALL TACK / PARK LED Model	Dots/m2	Pixel Pitch ( mm)	Pixel Composition	Lamp	Refresh rate	Scan Mode	Brightness (cd/m <sup>2</sup> )	HUB	Power Consumption W/m2	Average Power Consumption W/m2	Cabinet Size
Outdoor Full color P2.5-Q Pro	16000dots/m2	2,5	RGB	SMD1515	≥3840 HZ	Constant Current, 1/16 Scan	≥3500nits	HUB75	600W	210W	1920X1280MM
Outdoor Full color P3-Q Pro	105625 Dots/m <sup>2</sup>	3	RGB	SMD1515	≥3840 HZ	Constant Current, 1/13 Scan	≥4200nits	HUB75	720W	250W	1920X1280MM
Outdoor Full color P4-Q E	62500 dots/m2	4	RGB	SMD2525	≥1920 HZ	constant current:1/10 Scan	≥5000nits	HUB75	850W	270W	1920X1280MM
Outdoor Full color P5-Q E	40000dots/m2	5	RGB	SMD2727	≥1920 HZ	Constant Current, 1/8 Scan	≥5000nits	HUB75	750W	260W	1920X1280MM
Outdoor Full color P6.6-Q E	22500dots/m2	6,6	RGB	SMD3535	≥1920 HZ	Constant Current, 1/6 Scan	≥5000nits	HUB75	850W	270W	1920X1280MM
Outdoor Full color P8-Q E	15625dots/m2	8	RGB	SMD3535	≥1920 HZ	Constant Current, 1/5 Scan	≥4500nits	HUB75	800W	265W	1920X1280MM
Outdoor Full color P8-Q High	15625dots/m2	8	RGB	SMD3535	≥1920 HZ	Constant Current, 1/5 Scan	≥7000nits	HUB75	950W	350W	1920X1280MM